

# electrical connector caps **C SERIES**



Straight-sided, thin-wall closures designed to protect threaded connectors. Flanged end allows easy removal in hard-to-reach areas. Versatile design protects a variety of threaded and non-threaded applications.

### Specifications

- Material: Low-Density Polyethylene
- Colour: Red
- Applicable Spec: **NAS-813 MS-90376**

Part Number	To Cap Thread Size	Type II	Dimensions						Standard Package	
			A		B		C		Pieces	Lbs.
			in	mm	in	mm	in	mm		
C 2	1/2	-8	.476	12.09	.56	14.22	.50	12.70	7500	15
C 6	5/8	-10	.600	15.24	.68	17.27	.50	12.70	5000	12
C 8	3/4	-12	.724	18.39	.80	20.32	.50	12.70	5000	14
C 10	7/8	-14	.849	21.56	.93	23.62	.50	12.70	3000	11
C 12	1	-16	.974	24.74	1.05	26.67	.50	12.70	2500	11
C 14	1-1/8	-18	1.097	27.86	1.18	29.97	.56	14.22	2500	14
C 16	1-3/16	-	1.168	29.67	1.25	31.75	.56	14.22	1500	8
C 18	1-1/4	-20	1.221	31.01	1.30	33.02	.56	14.22	1500	9
C 20	1-3/8	-22	1.344	34.14	1.42	36.07	.56	14.22	1500	10
C 22	1-7/16	-	1.408	35.76	1.49	37.85	.56	14.22	1000	7
C 24	1-1/2	-24	1.467	37.26	1.55	39.37	.56	14.22	1000	7
C 26	1-3/4	-28	1.716	43.59	1.78	45.21	.56	14.22	1000	10
C 28	2	-32	1.964	49.89	2.04	51.82	.62	15.75	500	7
C 30	2-1/4	-36	2.210	56.13	2.29	58.17	.62	15.75	500	9
C 32	2-1/2	-40	2.460	62.48	2.54	64.52	.62	15.75	500	10
C 34	2-3/4	-	2.730	69.34	2.81	71.37	.62	15.75	500	10
C 36	3	-	2.980	75.69	3.06	77.72	.62	15.75	500	11
C 38	4	-	3.922	99.62	4.00	101.60	1.00	25.40	250	12
C 40	5	-	4.900	124.46	4.98	126.49	1.25	31.75	300	20

