

dome plugs **DOP SERIES**



Closes unneeded holes in chassis or other surfaces. Locks firmly into chassis or surfaces up to 1/8" thickness with quick and easy installation. Convex matte-finish head tapers to thin edge.

Specifications

- Material: Nylon 6 • Colour: Black
- Optional Colours: White and other colours available at extra charge (minimum quantities apply).
- Locking fingers in fractional increments up to maximum chassis thickness.
- Approximate head thickness: 0.063". Thickness may vary.

Part Number	Chassis Dimensions				Part Dimensions				Standard Package
	Maximum Thickness		Mounting Hole Dia.		C		D		
	in	mm	in	mm	in	mm	in	mm	
* DOP 187	.062	1.6	.187	4.7	.234	5.9	.250	6.4	1000
DOP 250	.062	1.6	.250	6.3	.312	7.9	.312	7.9	1000
DOP 312	.062	1.6	.312	7.9	.312	7.9	.375	9.5	1000
DOP 375	.125	3.2	.375	9.5	.406	10.3	.468	11.9	1000
DOP 437	.125	3.2	.437	11.1	.406	10.3	.531	13.5	1000
DOP 500	.125	3.2	.500	12.7	.406	10.3	.578	14.7	1000
DOP 562	.125	3.2	.562	14.3	.406	10.3	.656	16.7	1000
DOP 625	.125	3.2	.625	15.9	.406	10.3	.718	18.2	1000
DOP 687	.125	3.2	.687	17.5	.406	10.3	.781	18.2	1000
DOP 750	.125	3.2	.750	19.1	.406	10.3	.921	23.4	1000
DOP 812	.125	3.2	.812	20.6	.406	10.3	.890	22.6	1000
DOP 875	.125	3.2	.875	22.2	.406	10.3	1.016	25.8	1000
DOP 1000	.125	3.2	1.000	25.5	.453	11.5	1.203	30.5	500
DOP 1093	.125	3.2	1.093	27.8	.453	11.5	1.218	31.0	500
DOP 1187	.125	3.2	1.187	30.1	.453	11.5	1.312	33.3	500
DOP 1250	.125	3.2	1.250	31.7	.453	11.5	1.375	34.9	500
DOP 1375	.125	3.2	1.375	34.9	.453	11.5	1.500	38.1	500
DOP 1500	.125	3.2	1.500	38.1	.453	11.5	1.672	42.4	500
DOP 1750	.125	3.2	1.750	45.0	.453	11.5	1.925	48.9	500
DOP 2000	.125	3.2	2.000	50.8	.453	11.9	2.140	55.1	100

* Glossy-finish head.