

# electrical connector plugs *E SERIES*



Straight-sided, thin-wall closures designed to protect threaded connectors. Flanged end makes for easy removal in hard-to-reach areas. Versatile design will protect a variety of threaded and non-threaded applications.

### Specifications

- Material: Low-Density Polyethylene
- Colour: Yellow
- Applicable Spec: **NAS 820 MS-90376**

Part Number	Standard Thread Size	Type II	Dimensions								Standard Package	
			A		B		C		D		Pieces	Lbs.
			in	mm	in	mm	in	mm	in	mm		
E 2	1/2	-8A	.486	12.34	.426	10.82	.625	15.88	.66	16.76	10000	17
E 6	5/8	-10A	.607	15.42	.547	13.89	.625	15.88	.75	19.05	6500	14
E 10	3/4	-12A	.724	18.39	.664	16.87	.625	15.88	.84	21.34	5000	13
E 12	7/8	-14A	.850	21.59	.790	20.07	.625	15.88	1.00	25.40	4500	15
E 14	1	-16A	.977	24.82	.917	23.29	.625	15.88	1.16	29.46	3500	15
E 16	1-1/8	-18A	1.098	27.89	1.038	26.37	.625	15.88	1.25	31.75	2500	11
E 18	1-1/4	-20A	1.223	31.06	1.163	29.54	.625	15.88	1.38	35.05	1500	8
E 20	1-3/8	-22A	1.349	34.26	1.289	32.74	.625	15.88	1.50	38.10	1500	10
E 22	1-1/2	-24A	1.474	37.44	1.414	35.92	.625	15.88	1.62	41.15	1000	7
E 24	1-3/4	-28A	1.726	43.84	1.666	42.32	.625	15.88	1.88	47.75	1000	9
E 26	2	-32A	1.977	50.22	1.917	48.69	.625	15.88	2.09	53.09	1000	10
E 28	2-1/4	-36A	2.217	56.31	2.157	54.79	.625	15.88	2.38	60.45	500	6
E 30	2-1/2	-	2.418	61.42	2.358	59.89	.625	15.88	2.62	66.55	500	8

