

flared-fitting plugs **HF SERIES**



Designed to protect flared fittings as well as 37° flared fittings without gasket. Engineered with knurled head for ease of application. Will meet low-pressure testing requirements.

Specifications

- Material: High-Density Polyethylene
- Colour: Red

Part Number	To Plug Thread Size	To Plug Tubing Size	To Plug SAE/JIC Fitting	Dimensions						Standard Package	
				A		B		C		Pieces	Lbs.
				in	mm	in	mm	in	mm		
HF 4	3/8-24	3/16	3	.46	11.68	.56	14.22	.18	4.57	10000	12
HF 6	7/16-20	1/4	4	.50	12.70	.72	18.29	.22	5.59	5000	10
HF 8	1/2-20	5/16	5	.53	13.46	.81	20.57	.25	6.35	7500	18
HF 10	9/16-18	3/8	6	.53	13.46	.88	22.35	.28	7.11	5000	15
HF 11	5/8-18	3/8	—	.59	14.99	.94	23.88	.25	6.35	5000	13
HF 12	3/4-16	1/2	8	.75	19.05	1.06	26.92	.28	7.11	3000	14
HF 14	7/8-14	5/8	10	.84	21.34	1.25	31.75	.28	7.11	2000	12
HF 16	1-1/16-12	3/4	12	.86	21.84	1.41	35.81	.25	6.35	1500	12
HF 17	1-1/16-14	3/4	—	.86	21.84	1.41	35.81	.25	6.35	1000	6
HF 18	1-3/16-12	7/8	—	.93	23.62	1.50	38.10	.25	6.35	2500	25
HF 20	1-5/16-12	1	16	.91	23.11	1.75	44.45	.25	6.35	1000	12
HF 22	1-1/2-12	—	—	.93	23.62	1.81	45.97	.31	7.87	1000	17
HF 24	1-5/8-12	1-1/4	—	.94	23.88	2.22	56.39	.34	8.64	500	10
HF 26	1-3/4-12	—	—	.97	24.64	2.31	58.67	.34	8.64	500	12
HF 28	1-7/8-12	1-1/2	—	1.06	26.92	2.47	62.74	.38	9.65	500	12
HF 30	2-1/4-12	1-3/4	—	1.31	33.27	2.75	69.85	.38	9.65	250	9
HF 32	2-1/2-12	2	—	1.31	33.27	3.09	78.49	.38	9.65	250	9

