


## High Temperature Masking Discs



**Note:** Custom Die-Cut shapes and Diameters up to 18" are available upon request.

PART NUMBER	AVAILABLE MATERIAL	DIAMETER INCHES	DIAMETER MILLIMETERS	QTY PER ROLL
1/8" discs	POLYESTER/POLYIMIDE	.125	3.18	2,000
3/16" discs	POLYESTER/POLYIMIDE	.187	4.75	2,000
1/4" discs	POLYESTER/POLYIMIDE	.250	6.35	2,000
5/16" discs	POLYESTER/POLYIMIDE	.312	7.93	2,000
3/8" discs	POLYESTER/POLYIMIDE	.375	9.53	2,000
7/16" discs	POLYESTER/POLYIMIDE	.437	11.10	2,000
1/2" discs	POLYESTER/POLYIMIDE	.500	12.70	2,000
9/16" discs	POLYESTER/POLYIMIDE	.562	14.28	2,000
5/8" discs	POLYESTER/POLYIMIDE	.625	15.88	2,000
11/16" discs	POLYESTER/POLYIMIDE	.687	17.45	1,000
3/4" discs	POLYESTER/POLYIMIDE	.750	19.05	1,000
13/16" discs	POLYESTER/POLYIMIDE	.812	20.63	1,000
7/8" discs	POLYESTER/POLYIMIDE	.875	22.23	500
15/16" discs	POLYESTER/POLYIMIDE	.937	23.81	500
1" discs	POLYESTER/POLYIMIDE	1.000	25.41	500
1 1/16" discs	POLYESTER/POLYIMIDE	1.062	26.98	500
1 1/8" discs	POLYESTER/POLYIMIDE	1.125	28.58	500
1 3/16" discs	POLYESTER/POLYIMIDE	1.187	30.16	500
1 1/4" discs	POLYESTER/POLYIMIDE	1.250	31.76	500
1 5/16" discs	POLYESTER/POLYIMIDE	1.312	33.33	500
1 3/8" discs	POLYESTER/POLYIMIDE	1.375	34.93	500
1 7/16" discs	POLYESTER/POLYIMIDE	1.437	36.51	500
1 1/2" discs	POLYESTER/POLYIMIDE	1.500	38.11	500
1 9/16" discs	POLYESTER/POLYIMIDE	1.562	39.68	500
1 5/8" discs	POLYESTER/POLYIMIDE	1.625	41.29	250
1 11/16" discs	POLYESTER/POLYIMIDE	1.687	42.86	250
1 3/4" discs	POLYESTER/POLYIMIDE	1.750	44.46	250
1 13/16" discs	POLYESTER/POLYIMIDE	1.812	46.04	250
1 7/8" discs	POLYESTER/POLYIMIDE	1.875	47.64	250
1 15/16" discs	POLYESTER/POLYIMIDE	1.937	49.21	250
2" discs	POLYESTER/POLYIMIDE	2.000	50.81	100
3" discs	POLYESTER/POLYIMIDE	3.000	76.22	100
4" discs	POLYESTER/POLYIMIDE	4.000	101.63	100

**Polyester or Polyimide.**

### POLYESTER

Withstands temperatures up to 204°C/400°F. Request samples from our Sales Department for testing **BEFORE** using in your application.

### POLYIMIDE

Withstands temperatures up to 260°C/500°F (1mil film thickness). Withstands up to 315°C/600°F (2mil film thickness). Request samples from our Sales Department for testing **BEFORE** using in your application.

There are new sizes and styles of masks becoming available on a regular basis, please contact our Sales Department.

For fast service and free samples, call: 1-800-668-3235 Fax: 1-905-791-3178 or Email: sales@capsnplugs.com

11-1