

inverted flared-fitting plugs *HT SERIES*



Designed to protect inverted flare fittings. Engineered with knurled head for ease of application. Will meet low-pressure testing requirements.

Specifications

- Material: Low-Density Polyethylene
- Colour: Red
- Applicable Spec: **MIL-C-52078**

Part Number	To Plug Standard Thread Size	To Plug Tubing Size	Dimensions						Standard Package	
			A		B		C		Pieces	Lbs.
			in	mm	in	mm	in	mm		
HT 2	5/16-28	1/8	.22	5.59	.44	11.18	.19	4.83	5000	5
HT 4	3/8-24	3/16	.25	6.35	.50	12.70	.19	4.83	5000	6
HT 6	7/16-24	1/4	.27	6.86	.63	16.00	.19	4.83	5000	8
HT 8	1/2-20	5/16	.28	7.11	.69	17.53	.25	6.35	5000	11
HT 10	5/8-18	3/8	.31	7.87	.81	20.57	.25	6.35	5000	13
HT 12	3/4-18	1/2	.31	7.87	.87	22.10	.25	6.35	5000	15
HT 14	7/8-18	5/8	.38	9.65	.87	22.10	.25	6.35	5000	17
HT 16	1-1/16-16	3/4	.43	10.92	1.19	30.23	.25	6.35	2500	13

