

tube caps LONG

non-threaded caps

Part Number	To Fit Diameter		Dimension		Standard Package	
	in	A mm	in	B mm	Pieces	Lbs.
214-L	15/64	5.94	1.13	28.70	15000	18
216-L	3/8	4.78	1.12	28.45	7500	15
1030	27/64	10.72	1.25	31.75	5000	12
217-L	7/16	11.13	1.50	38.10	5000	14
1834	5/8	15.88	2.50	63.50	1000	9
220-U	5/8	15.88	1.50	38.10	2000	9
222-L	3/4	19.05	2.47	62.74	4000	27
201-M	7/8	22.23	1.75	44.45	1000	9
138-L	1	25.40	1.75	44.45	1000	9
289-M	1-1/4	31.75	1.50	38.10	700	7
289-L	1-1/4	31.75	1.75	44.45	500	6
428	1-3/8	34.93	1.50	38.10	500	6
428-2	1-3/8	34.93	1.59	40.39	500	7
290-L	1-1/2	38.10	1.75	44.45	500	10
291-L	1-5/8	41.28	1.25	31.75	500	6
291-3	1-27/32	46.84	1.21	30.73	500	7
226-L	2	50.80	1.53	38.86	250	5



Designed to protect the ends of threaded and non-threaded tubing, rods or packaging tubes with a friction-fit straight-wall design. Used extensively for masking of painting, plating and sandblasting operations.

Specifications

- Material: Low-Density Polyethylene
- Colour: Orange
- Will fit diameters matching inside (A) dimension
- Applicable Spec: MIL-C-5501/9

