



HiTemp Green Polyester Masking Tape

PART NUMBER	MATERIAL	WIDTH INCHES	WIDTH MILLIMETERS	THICKNESS (MILS)	YARDS PER ROLL
PTape 1/4"	POLYESTER	.250	6.35	2	72
PTape 1/2"	POLYESTER	.500	12.70	2	72
PTape 3/4"	POLYESTER	.750	19.05	2	72
PTape 1"	POLYESTER	1.000	25.41	2	72
PTape 1 1/2"	POLYESTER	1.500	38.11	2	72
PTape 2"	POLYESTER	2.000	50.81	2	72

Standard tape widths up to 6" available. Larger custom widths are also available.

Flat Profile Self-Fusing Silicone Tape (Non-Adhesive)

PART NUMBER	WIDTH (INCHES)	THICKNESS (MILS)	YARDS/ROLL
SIL-8	.500	10	18
SIL-12	.750	10	18
SIL-16	1.000	10	18

Triangular Profile Self-Fusing Silicone Tape (Non-Adhesive)

PART NUMBER	WIDTH (INCHES)	THICKNESS (MILS)	YARDS/ROLL
SIL-16H	1.000	20	12
SIL-24H	1.500	20	12
SIL-32H	2.000	20	12

HiTemp Amber Polyimide Masking Tape

PART NUMBER	MATERIAL	WIDTH INCHES	WIDTH MILLIMETERS	THICKNESS (MILS)	YARDS PER ROLL
KTape 1/4"	POLYIMIDE	.250	6.35	1	36
KTape 1/2"	POLYIMIDE	.500	12.70	1	36
KTape 3/4"	POLYIMIDE	.750	19.05	1	36
KTape 1"	POLYIMIDE	1.000	25.41	1	36
KTape 1 1/2"	POLYIMIDE	1.500	38.11	1	36
KTape 2"	POLYIMIDE	2.000	50.81	1	36

Standard tape widths up to 6" available. Larger custom widths are also available.

POLYESTER

Withstands temperatures up to 204°C/400°F. Request samples from our Sales Department for testing **BEFORE** using in your application.

POLYIMIDE

Withstands temperatures up to 260°C/500°F (1mil film thickness). Withstands up to 315°C/600°F (2mil film thickness). Request samples from our Sales Department for testing **BEFORE** using in your application.

SILICONE

A true high performance, general purpose insulator and high-temperature mask. It is an excellent electrical insulator and will withstand temperatures up to 260°C/500°F.