

o-ring face-fitting caps **OF SERIES** (PATENT PENDING)



Six internal ribs create a positive grip on the outer surfaces of the fittings nut. Three internal webs act as a positive stop and positioning feature, thus preventing movement which could lead to contamination or damage to the fitting during installation.

Specifications

- Material: Low-Density Polyethylene
- Colour: Orange

Part Number	To Cap Thread Size	Fitting Size	Dimensions						Standard Package	
			A		B		C		Pieces	Lbs.
			in	mm	in	mm	in	mm		
OF 4	9/16	-4	.675	17.15	.32	8.13	.49	12.45	3500	11
OF 6	11/16	-6	.790	20.07	.37	9.40	.57	14.48	2500	10
OF 8	13/16	-8	.916	23.27	.43	10.92	.73	18.54	3000	18
OF 10	1	-10	1.108	28.14	.53	13.46	.83	21.08	2000	17
OF 12	1-13/16	-12	1.360	34.54	.57	14.48	.93	23.62	1000	12
OF 16S	1-7/16	-16	1.580	40.89	.58	14.73	1.00	25.40	900	15
OF 16	1-7/16	-16	1.610	40.13	.58	14.73	1.00	25.40	900	15
OF 20	1-11/16	-20	1.860	47.24	.58	14.73	1.00	25.40	700	14
OF 24	2-12	-24	2.230	56.64	.58	14.73	1.00	25.40	450	12

