



SPP SERIES PULL PLUGS

silicone pull plugs

PART NUMBER	I N C H E S				M I L L I M E T E R S				PLUG THREAD SIZE	QTY PER BAG
	A	B	C	D	A	B	C	D		
SPP .062	0.062	0.046	0.375	0.337	1.570	1.170	9.530	8.560		1,000
SPP .073	0.073	0.046	0.612	0.590	1.850	1.170	15.540	14.990		1,000
SPP .080	0.080	0.045	1.000	1.000	2.030	1.140	25.400	25.400		1,000
SPP .093	0.093	0.050	0.625	0.625	2.360	1.270	15.880	15.880		1,000
SPP .109	0.109	0.062	0.625	0.625	2.770	1.570	15.880	15.880	4-40	1,000
SPP .125	0.125	0.062	0.625	0.625	3.180	1.570	15.880	15.880	6-32	1,000
SPP .130LSI	0.130	0.093	1.000	1.000	3.300	2.360	25.400	25.400		1,000
SPP .140	0.140	0.085	0.625	0.625	3.560	2.160	15.880	15.880		1,000
SPP .156	0.156	0.062	0.625	0.625	3.960	1.570	15.880	15.880	8-32	1,000
SPP .175	0.175	0.123	1.250	1.250	4.450	3.120	31.750	31.750	M5, 3/16, 10-32	500
SPP .187	0.187	0.110	0.625	0.625	4.750	2.790	15.880	15.880		500
SPP .195S	0.195	0.110	0.625	0.625	4.950	2.790	15.880	15.880		500
SPP .218	0.218	0.130	1.000	1.000	5.540	3.300	25.400	25.400	M6, 1/4-20	500
SPP .225	0.225	0.125	1.000	1.000	5.720	3.180	25.400	25.400		500
SPP .257	0.257	0.130	1.000	1.000	6.530	3.300	25.400	25.400		500
SPP .275	0.275	0.125	0.937	0.920	6.990	3.180	23.800	23.370		500
SPP .281	0.281	0.138	1.000	1.000	7.140	3.510	25.400	25.400	M8, 5/16-18	500
SPP .312	0.312	0.147	1.000	1.000	7.920	3.730	25.400	25.400		250
SPP .335	0.335	0.153	1.000	1.000	8.510	3.890	25.400	25.400	3/8-16	250
SPP .350	0.350	0.193	0.900	1.000	8.890	4.900	22.860	25.400	3/8-16, M10	250
SPP .388	0.388	0.157	1.000	1.000	9.860	3.990	25.400	25.400	7/16-14	250
SPP .408	0.408	0.191	1.009	1.000	10.360	4.850	25.630	25.400		250
SPP .445	0.445	0.255	1.000	1.000	11.300	6.480	25.400	25.400	1/2-13, M12	250
SPP .472	0.472	0.243	1.000	1.000	11.990	6.170	25.400	25.400		100
SPP .510	0.510	0.256	1.000	0.956	12.950	6.500	25.400	24.280	M14	100
SPP .530	0.530	0.250	1.000	1.000	13.460	6.350	25.400	25.400		100
SPP .551	0.551	0.250	1.181	1.181	14.000	6.250	30.000	30.000		100
SPP .570	0.570	0.312	1.000	1.000	14.480	7.920	25.400	25.400	M16	100
SPP .590	0.590	0.250	1.000	1.000	14.990	6.350	25.400	25.400		100
SPP .612	0.612	0.250	1.000	1.000	15.540	6.350	25.400	25.400		100
SPP .620	0.620	0.329	1.500	1.500	15.750	8.360	38.100	38.100		100
SPP .640	0.640	0.375	1.000	1.000	16.260	9.530	25.400	25.400		100
SPP .670	0.670	0.470	1.500	1.500	17.020	11.940	38.100	38.100		100
SPP .700	0.700	0.375	1.250	1.250	17.780	9.530	31.750	31.750	M20	100
SPP .729	0.729	0.315	1.000	1.000	18.520	8.000	25.400	25.400		100
SPP .750	0.750	0.375	1.000	1.000	19.050	9.530	25.400	25.400		100

Major diameter of Pull Plugs up to 1.450" are available. Contact our Sales Department.

- when pulled through holes, the larger diameter (A) stretches and diameter compresses until released providing a tight seal, even helping to plug the thread chamfers on threaded applications.
- smaller diameter (B) pull tab and chamfer transition to major diameter aids easy application.
- the major diameter (A) of the pull plug should be at least 4-5% larger than the hole to be plugged.
- temperature resistant up to 315°C / 600°F and durable for repeat use.