

threaded (straight) cap TC SERIES



Designed to protect straight threads on studs and fittings. Rolled threads allow you to either push or thread on. Tight seal makes an ideal mask for painting or plating, as well as a deterrent for contaminants.

Specifications

- Material: Low-Density Polyethylene
- Colour: Orange
- Applicable Spec:
MIL-C-5501/1 (NAS-814)
MIL-C-5501/3

Part Number	To Cap Thread Size	Tubing Size	Dimensions A		Standard Package	
			in	mm	Pieces	Lbs.
TC 1	3/8-24	3/16	.47	11.94	15000	14
TC 2	7/16-20	1/4	.47	11.94	15000	17
TC 3	7/16-24	1/4	.31	7.87	10000	10
TC 40	1/2-20	5/16	.50	12.70	5000	6
TC 4	1/2-20	5/16	.50	12.70	10000	16
TC 42	1/2-20	5/16	.88	22.35	5000	11
TC 5	9/16-18	3/8	.50	12.70	7500	12
TC 6	5/8-18	3/8	.47	11.94	7500	15
TC 62	5/8-18	3/8	.59	14.99	5000	12
TC 63	5/8-18	3/8	.75	19.05	5000	15
TC 7	5/8-24	-	.38	9.65	10000	15
TC 8-S	3/4-16	1/2	.50	12.70	5000	13
TC 8	3/4-16	1/2	.56	14.22	5000	14
TC 8-R	3/4-16	1/2	.63	16.00	4500	14
TC 82	3/4-18	-	.69	17.53	5000	15
TC 9	3/4-20	-	.50	12.70	5000	11
TC 10	7/8-14	5/8	.72	18.29	5000	21
TC 111	7/8-18	5/8	.78	19.81	5000	19
TC 100	7/8-20	5/8	.72	18.29	4000	15
TC 120	1-20	-	.78	19.81	2000	11
TC 13	1-1/16-12	3/4	.75	19.05	2000	11
TC 14	1-1/16-14	3/4	.75	19.05	1500	11
TC 15	1-1/8-18	-	.47	11.94	2500	15
TC 17	1/1/4-18	-	.47	11.94	2000	16
TC 18	1-5/16-12	1	.88	22.35	1000	8
TC 19	1-3/8-18	1	.47	11.94	1500	14
TC 20	1-5/8-12	1-1/4	.91	23.11	750	8
TC 21	1-7/8-12	1-1/2	1.00	25.40	700	10

