

# unified sealing plug **UT SERIES**



Designed to protect unified/straight threaded ports. Each plug features a unique and integral Tight Fit™ sealing lip along with five complete threads. This design prevents contaminants from entering or fluids from escaping fittings or ports...without the need of an o-ring. UT Series can be applied or removed with a screwdriver, socket wrench, power tool or by hand.

### Specifications

- High-Density Polyethylene
- Color: Red
- Optional Material: Nylon 6 (yellow)

Part Number	To Plug Thread Size	Dimensions						Standard Package	
		in	A mm	in	B mm	in	C mm	Pieces	Lbs.
UT 6	7/16-20	0.43	11.00	0.82	20.80	0.35	9.00	7000	30
UT 8	1/2-20	0.43	11.00	0.90	22.80	0.39	10.00	5500	33
UT 10	9/16-18	0.43	11.00	0.98	24.80	0.39	10.00	4700	29
UT 11	5/8-18	0.47	12.00	0.98	24.80	0.47	12.00	3500	32
UT 12	3/4-16	0.39	10.00	1.02	26.00	0.51	13.00	3000	26
UT 14	7/8-14	0.55	14.00	1.33	33.80	0.47	12.00	1700	24
UT 16	1-1/16-12	0.55	14.00	1.61	40.80	0.47	12.00	1200	25
UT 20	1-5/16-12	0.59	15.00	1.65	42.00	0.59	15.00	750	18
UT 24	1-5/8-12	0.67	17.00	2.28	57.80	0.59	15.00	400	16

